


* reduced tightening torque
TA=30 Nm for bore diameter D > Ø30



material

safety part: heat-treated steel
clamping hub: high-tensile aluminum
bellows: stainless steel
screws: ISO 4762 / 12.9

Technical Data:

setting range: 40 – 100 Nm
torsional stiffness: 20 Nm/arcmin
max. axial shaft displacement: ± 0,6 mm
max. lateral shaft displacement: 0,2 mm
mass: ca. 1,9 kg
moment of inertia: 1,5 · 10⁻³ kgm²
ØD1 min/max: 14 / 38 mm
ØD2 min/max: 18 / 35 mm
temperature range: -30°C up to +200°C

| | | | | | | | |
|--------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------|----------|----------|---------------------------------------------------------------------------------------|--------------------------------------------------------------|-----------------|---------|
| | | Änderung | | | Werkstoffbezeichnung | Werkstoffnummer | Maßstab |
| | | | | | - | - | |
| | | | | | Rohteil-/Vorteilnummer | Gewicht | 1:1 |
| | | | | | - | - kg | |
| | | gepr. | | | safety coupling SKB - KP 100 | | |
| | | | | | | | |
| Passung | Abmaß | gez. | 22.05.17 | Be | Benennung Format A3 Artikelnummer Ersatz für | | |
| DIN ISO 13715  | DIN ISO 2768-mK 0,5 ... 6 ± 0,1 6 ... 30 ± 0,2 30 ... 120 ± 0,3 120 ... 315 ± 0,5 315 ... 1000 ± 0,8 | | Datum | Name | | | |
| | | | |  | MB - 141 17803-e | | |
| | | | | D-63839-Kleinwallstadt | ersetzt durch | | |