



M5 - ISO 4762 - TA=5Nm

technical Data:

nominal torque: 10 Nm

maximum torque: 14 Nm

torsional stiffness: 0,04 Nm/arcmin

max. radial shaft displacement: 51 mm

max. axial shaft displacement: ± 1,5 mm

mass: 3,1 kg

moment of inertia: 0,17 10⁻³ kgm²

max. speed: 150 min⁻¹

D1 - D2 min/max: 7/15 mm

temperature range: -40 up to +350 °C

material:

bellows: stainless steel 1.4571

hubs: stainless steel 1.4301

intermediate pipe: stainless steel

screws: ISO 4762 stainless steel/ A4-80

optionally 12.9 - nickel plated

		Änderung	Werkstoffbezeichnung		Werkstoffnummer	Maßstab
			-		-	
			Rohteil-/Vorteilnummer		Gewicht	
			-		- kg	1:1
			Metal Bellows Coupling with Intermediate Pipe			
			WD-VA 10 - L=3m			
Passung	Abmaß	gez.	08.09.15	Be	Benennung	
DIN ISO 13715	DIN ISO 2768-mK		Datum	Name	Format A4	Artikelnummer
	0,5 ... 6 ± 0,1		JAKOB Antriebstechnik		MB-140 22361-3m-e	
	6 ... 30 ± 0,2		D-63839-Kleinwallstadt		Ersatz für	
	30 ... 120 ± 0,3				-	
	120 ... 315 ± 0,5				ersetzt durch	
	315 ... 1000 ± 0,8				-	